

LIST OF CURRENT CLAIMS

Claims 1 – 84 (Canceled).

Claim 85 (Currently Amended). A corner joint comprising two frame side members having attachment channels and mitered end portions, and at least one corner piece having two insert parts joined at connecting ends and positioned relative to one another at a predetermined angle, each insert part configured to be received by the mitered end portions of a respective one of the attachment channels of the side members,

the attachment channels being confined by an inner wall and an outer wall,

wherein a mutual interlocking between the corner piece and the frame side members is carried out by lips defined by a pressed-in material part of the outer wall, which said lips cooperate with notches defined on the corner piece;

wherein each insert part includes at least one said notch comprising a triangular shape defined by a first side against which the lip is positioned which is longer than a second side over which a free end of the lip projection is pressed in;

wherein the lips generate a pre-stress in the form of pressure on both frame side members and tension in the corner piece, the material of the lips being compressed from a first length to a second length, which is shorter than the first length; and

wherein a compression force has been created in each of the frame side members ends by pushing off both frame side members respectively on the lips;

the corner piece comprising inclined parts defining a pressure zone between the lips and a place on the inner wall which is situated deeper in the attachment channels than the lips to provide a pressure between said place and the lips;

[[the]] each insert part ~~parts~~ being equipped with a resilient member, which resilient members ~~which~~ are connected to one another at an angle; and

the inclined parts being respectively connected to free ends of the resilient members;

wherein a free space or clearance free of material is provided on an outside corner of the corner piece, the free space or clearance extending from the lips to at least the connecting end of the insert parts;

wherein the inclined parts create tensile forces in the resilient members, since a ~~[[the]]~~ pressure in the inclined parts results in a tension in the resilient members;

the tensile forces in the resilient members resulting in pressure forces in the outer and inner walls, thus contributing to rigidity and the pre-stress of the corner joint as a whole;

wherein the resilient members are positioned generally along and in contact with the inner wall of the respective attachment channel.

Claim 86 (Currently Amended). The corner joint according to claim 85, wherein the second side extends substantially perpendicular to the longitudinal direction of the lip ~~projection~~.

Claim 87 (Previously Presented). The corner joint according to claim 86, wherein said second side of the at least one notch, over which the free end of the lip projection is pressed in, has a bent shape.

Claim 88 (Previously Presented). The corner joint according to claim 85 wherein stop-parts are situated behind the pressed-in lips, the stop parts include serrations.

Claim 89 (Previously Presented). The corner joint according to claim 85, wherein each of said insert parts includes an end portion geometrically configured in the shape of a triangle having an apex directed along a longitudinal axis of the respective attachment channel, each insert part defining a second leg arranged to be urged against the inner wall of the respective attachment channel, a first leg connecting at a first end with a first end of the second leg to form the apex and extending at an oblique angle relative to the second leg in a direction generally proximal to the corner portion, and a third leg extending obliquely relative to the second leg in a direction generally proximal to the corner portion and connecting to the second leg.

Claim 90 (Previously Presented). The corner joint according to claim 89, wherein each inclined part is a fragment of the first leg of the corresponding insert part.

Claim 91 (Currently Amended). The corner joint according to claim 90, wherein the corner joint further comprises a panel being wedged up by wedges, wherein the middle of the wedges is situated in [[a]] an imaginary prolongation of the inclined parts.

Claim 92 (Currently Amended). The corner joint according to claim 89, wherein each of the insert parts includes the resilient member comprising said second leg and a connecting leg situated in an extension of said second leg for connecting the end portions with the connecting ends of the insert parts; the end portion and the resilient member of each of said insert parts connected to one another at an angle so that the resilient members provide a reactive tensile force to the compression force which occurs in the frame side members ends and which have been created by pushing off both frame side members on the notch of the corner piece.

Claims 93-94 (Canceled).

Claim 95 (Currently Amended). The corner joint according to any one of the preceding claims, wherein the corner piece is provided with positioning elements arranged to guide the insert parts into the attachment channels ~~when positioned therein~~; and,

wherein the positioning elements include at least one of the following elements;

elastic press-on elements provided on the corner piece to push [[the]] inner sides of the insert parts against an inner wall of the respective attachment channel;

elastically bendable flaps provided on the insert parts at a predetermined distance from the connecting ends thereof and arranged to cooperate with the outer wall of the respective attachment channel;

guiding elements provided on the corner piece in the shape of a little leg having elastically bendable flaps on the corner piece arranged to cooperate with the outer wall of the respective attachment channel.

Claim 96 (Previously Presented). The joint according to claim 95, wherein the corner piece includes a clearance generally defined at an inside corner where the insert parts connect and having a hook shaped profile.